

11 Comber Road, Carryduff, BELFAST, BT8 8AN Tel: 028 9081 4777 Fax: 028 9081 2881 Website: <u>www.kitchenmaster-ni.com</u> Email: <u>sales@kitchenmaster-ni.com</u>

TECHNICAL SPECIFICATION

DRAIN OPENER

This product has been specially formulated to unblock drains without the use of sulphuric acid which is highly corrosive and difficult to handle for both manufacturers and end users. It is based on a blend of chlorine based bleaching agents, caustic soda and anionic surfactants which will clear blocked and slow running sinks, basins, bath/shower plugholes and pipes effortlessly.

Features include:

- Highly viscous to reduce risk of splashing during use.
- Clears drains fast and effortlessly.
- High specific gravity means that it is heavier than water and can sink through standing water down the U-bend to the blockage.
- Powerful caustic formulation dissolves food waste, hairs and loosens grease.
- Sodium hydroxide reacts with fatty acids (grease) to produce a form of soap which is easily dissolved and washed away.
- Will not damage septic tanks, pipework or plastic drums.
- All surfactants used are biodegradable and phosphate free.

PROPERTIES:

Appearance @ 20°C pH neat Odour Specific Gravity @ 20°C Flammability **SPECIFICATION:**

Milky, highly viscous liquid 14 Chlorinated 1.21 +/- 0.003 Non-flammable

DIRECTIONS FOR USE:

- For blocked or slow running plugholes, pour 500ml of product slowly down drain.
- Store at room temperature and SHAKE WELL BEFORE USE.
- Leave to work for 30 minutes.
- Flush with hot water from tap.
- For tough clogs, leave to work overnight.

STORAGE:

Store in original container and protect from extremes of temperature. Do not store in direct sunlight nor allow the product to freeze. Shelf life (in unopened original container) is a minimum of 18 months. Do not mix with acidic product (i.e. toilet cleaner), as toxic fumes will be given off.

SAFETY ADVICE:

Under the new GHS Standard this product is classified as Corrosive and Toxic to aquatic organisms. Please refer to section 2.2 of the Safety Data Sheet for more information.

PACK SIZES:

• 4x5L case (48 per pallet)

Order Code: INDDRAIN-4X5L