



11 Comber Road, Carryduff, BELFAST, BT8 8AN  
Tel: 028 9081 4777 Fax: 028 9081 2881  
Website: [www.kitchenmaster-ni.com](http://www.kitchenmaster-ni.com) Email: [sales@kitchenmaster-ni.com](mailto:sales@kitchenmaster-ni.com)

## TECHNICAL SPECIFICATION

### FLOOR MAINTAINER

An aqueous based floor maintainer for use as part of a floor care system. It is particularly effective to maintain "Wet Look" systems in conjunction with ultra high speed buffing machines. The product is an opaque bright pink liquid with a pleasant floral fragrance. It contains a blend of polymer dispersions, surfactants, fragrance, preservative and water soluble dyes.

#### Features include:

- Economical dilution rates.
- Gives excellent results on all metallised polishes and wet look systems.
- May be used by damp mopping and spray burnishing.
- May be used on non-porous floors such as rubber and pure vinyl without the use of polish or seal.
- Improves resistance to slip.
- Biocidal effect allows safe use for areas such as hospitals and nursing homes.
- Highly fragranced to leave room smelling clean and fresh.
- Surfactants used are biodegradable and phosphate free.

#### PROPERTIES:

Appearance @ 20°C  
pH (neat)  
Odour  
Specific Gravity @ 20°C  
Flammability

#### SPECIFICATION:

Bright pink, clear, non viscous liquid  
6.5 +/- 0.5  
Sweet floral fragrance  
1.000 +/- 0.002  
Non-flammable

#### DIRECTIONS FOR USE:

- Heavily soiled floors should be swept and if necessary, scrubbed with a neutral detergent before applying.
- **DAMP MOPPING:** Dilute 1 part with 30 parts water. Mop floor with this mixture and allow to dry. Machine buff using a rotary machine to give a tough, wear resistant gloss film.
- **SPRAY BURNISH :** Dilute 1 part with 20 parts water. Spray this mixture onto the floor (1-2 square meters at a time) and machine buff. If using ultra high speed machines, dilute with 5 parts water.
- Only use pads which are recommended for buffing.
- Never use pads which have been used to buff spirit waxes.
- Not suitable for use on unsealed wood and cork flooring.

#### STORAGE:

Store in original container and protect from extremes of temperature. Do not store in direct sunlight nor allow the product to freeze. Shelf life (in unopened original container) is a minimum of 18 months.

#### SAFETY ADVICE:

Under the new GHS Standard this product is not classified. Please refer to section 2.2 of the Safety Data Sheet for more information.

#### PACK SIZE:

4X5L case (48 per pallet)

Order Code: FLRMAINT-4X5L