

SAFETY DATA SHEET

Floor Stripper

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Floor Stripper

Product no.

FLRSTRIP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning agent.

Restricted to professional users.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Kitchenmaster NI Ltd

11 Comber Road,

BT8 8AN Belfast

United Kingdom

028 9081477 02890812881

sales@kitchenmaster-ni.com

E-mail

sales@kitchenmaster-ni.com

Revision

03/10/2024

SDS Version

1.0

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

Emergency contact number (Kitchenmaster): +44 (0)28 9081 4777 (8.30am - 5pm, Monday - Thursday; 8.30am - 4pm Friday)

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Met. Corr. 1; H290, May be corrosive to metals.

Skin Corr. 1B; H314, Causes severe skin burns and eye damage.

Eye Dam. 1; H318, Causes serious eye damage.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

May be corrosive to metals. (H290)
Causes severe skin burns and eye damage. (H314)

Precautionary statement(s)

General

-

Prevention

Do not breathe vapour/mist. (P260)
Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. (P303+P361+P353)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

Storage

Store in a container with a resistant inner liner. (P406)

Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

2-aminoethanol;ethanolamine
Disodium metasilicate
sodium hydroxide;caustic soda
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Additional labelling

Not applicable.

Labelling of contents according to Detergents Regulation (EC) No 648/2004 as retained and amended in UK law < 5%

- Amphoteric surfactants
- Non-ionic surfactants

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
2-aminoethanol;ethanolamine	CAS No.: 141-43-5 EC No.: 205-483-3 UK-REACH: Index No.: 603-030-00-8	3-5%	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 4, H332 STOT SE 3, H335 (SCL: 5.00 %) Aquatic Chronic 3, H412	[1]
Disodium metasilicate	CAS No.: 6834-92-0 EC No.: 229-912-9 UK-REACH: Index No.: 014-010-00-8	1-3%	Met. Corr. 1, H290 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	

2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0 UK-REACH: Index No.: 603-014-00-0	1-3%	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]
sodium hydroxide;caustic soda	CAS No.: 1310-73-2 EC No.: 215-185-5 UK-REACH: Index No.: 011-002-00-6	1-3%	Met. Corr. 1, H290 Skin Corr. 1A, H314 Skin Corr. 1B, H314 (SCL: 2.00 %) Skin Irrit. 2, H315 (SCL: 0.50 %) Eye Dam. 1, H318 (SCL: 2.00 %) Eye Irrit. 2, H319 (SCL: 0.50 %)	
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts	CAS No.: 97862-59-4 EC No.: 931-296-8 UK-REACH: Index No.:	1-3%	Eye Dam. 1, H318 Aquatic Chronic 3, H412	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed



According to REACH Regulation (EC) No 1907/2006, as retained and amended by SI 2019/758 and SI 2020/1577

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

May attack metals releasing highly flammable gas (hydrogen).

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO₂)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact

The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: 2X

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Store in a container with a resistant inner liner.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Store locked up.

Store protected from heat and direct sunlight.

Incompatible materials

Metals

Metal salts.
Acids
Organic material
Strong oxidising agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-aminoethanol;ethanolamine

Long term exposure limit (8 hours) (ppm): 1

Long term exposure limit (8 hours) (mg/m³): 2,5

Short term exposure limit (15 minutes) (ppm): 3

Short term exposure limit (15 minutes) (mg/m³): 7,6

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 25

Long term exposure limit (8 hours) (mg/m³): 123

Short term exposure limit (15 minutes) (ppm): 50

Short term exposure limit (15 minutes) (mg/m³): 246

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

sodium hydroxide;caustic soda

Short term exposure limit (15 minutes) (mg/m³): 2

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	7.5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	12.5 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	13.04 mg/m ³
Long term – Systemic effects - Workers	Inhalation	44 mg/m ³
Long term – Systemic effects - General population	Oral	7.5 mg/kg bw/day

2-butoxyethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	59 mg/m ³
Long term – Systemic effects - Workers	Inhalation	98 mg/m ³
Short term – Local effects - General population	Inhalation	147 mg/m ³
Short term – Local effects - Workers	Inhalation	246 mg/m ³
Short term – Systemic effects - General population	Inhalation	426 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1091 mg/m ³
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day

Disodium metasilicate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	740 µg/kg bw/day
Long term – Systemic effects - Workers	Dermal	1.49 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	1.55 mg/m ³
Long term – Systemic effects - Workers	Inhalation	6.22 mg/m ³
Long term – Systemic effects - General population	Oral	740 µg/kg bw/day

sodium hydroxide;caustic soda

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	1 mg/m ³
Long term – Local effects - Workers	Inhalation	1 mg/m ³

PNEC

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		13.5 µg/L
Freshwater sediment		11.1 mg/kg
Marine water		1.35 µg/L
Marine water sediment		1.11 mg/kg
Sewage treatment plant		3 g/L
Soil		850 µg/kg

2-butoxyethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg
Marine water		0.88 mg/L
Marine water sediment		3.46 mg/kg
Sewage treatment plant		463 mg/L
Soil		2.33 mg/kg

Disodium metasilicate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		7.5 mg/L
Intermittent release (freshwater)		7.5 mg/L
Marine water		1 mg/L
Sewage treatment plant		1 g/L

8.2. Exposure controls

Apply general control to prevent unnecessary exposure

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

Appropriate technical measures

Ensure that eyewash stations and safety showers are located within easy reach.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed

thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure


Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment


Generally

Use only UKCA marked protective equipment.


Respiratory Equipment

Work situation	Type	Class	Colour	Standards	
Where risk assessment shows air-purifying respirators are appropriate.	Combination filter ABEK-P2	Class 1/2	Brown/Gray/Yellow /Green/White	EN14387	


Skin protection

Work situation	Recommended	Type/Category	Standards	
In the event of a risk of splashing.	Chemical resistant clothing and shoes	EN 943	EN 943	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Butyl	0,35	> 480	EN374-2, EN374-3, EN388	

Eye protection

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Clear, Red

Odour / Odour threshold

Characteristic

pH

>13

Density (g/cm³)

1.03-1.045 (20 °C)

Kinematic viscosity

No information available as testing has not been completed.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

No information available as testing has not been completed.

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)

No information available as testing has not been completed.

Vapour pressure

No relevant or available data due to the nature of the product.

Relative vapour density

No relevant or available data due to the nature of the product.

Decomposition temperature (°C)

No information available as testing has not been completed.

Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to nature of the product.

Flammability (°C)

No relevant or available data due to the nature of the product.

Auto-ignition temperature (°C)

No information available as testing has not been completed.

Lower and upper explosion limit (% v/v)

No relevant or available data due to the nature of the product.

Solubility

Solubility in water

Soluble

n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.

Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

9.2. Other information

Oxidizing properties

Testing not relevant or not possible due to nature of the product.

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

May attack metals releasing highly flammable gas (hydrogen).

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

See section 10.1 for further information.

10.4. Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5. Incompatible materials

Metals

Metal salts.

Acids

Organic material

Strong oxidising agents.

10.6. Hazardous decomposition products

Thermal decomposition may produce corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

We have not carried out any animal testing for this product. Any ATE figures quoted below are from toxicity classifications that have been carried out using ATE (Acute Toxicity Estimate) calculation method, using LD50 or ATE figures provided by the raw material manufacturer.

Acute toxicity

Product/substance	2-aminoethanol;ethanolamine
Species:	Rat
Route of exposure:	Oral
Test:	LD50

According to REACH Regulation (EC) No 1907/2006, as retained and amended by SI 2019/758 and SI 2020/1577

Result:	1087 mg/kg
Product/substance	2-aminoethanol;ethanolamine
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	2504 mg/kg
Product/substance	2-aminoethanol;ethanolamine
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	1487 mg/m ³
Product/substance	Disodium metasilicate
Species:	Rat
Route of exposure:	Oral
Test:	LC50
Result:	1152-1349 mg/kg
Product/substance	Disodium metasilicate
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	> 2.06 g/m ³
Product/substance	Disodium metasilicate
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	> 5000 mg/kg
Product/substance	2-butoxyethanol
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LC50
Result:	1300 mg/kg
Product/substance	2-butoxyethanol
Species:	Guinea pig
Route of exposure:	Inhalation
Test:	LC0
Result:	>3.1 mg/L
Product/substance	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	2335 mg/kg
Product/substance	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Product/substance 2-butoxyethanol

Test method: OECD 405
 Species: Rabbit
 Duration: 24 hours
 Result: Adverse effect observed (Irritating)

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Product/substance: Disodium metasilicate
 Species: Rat
 Route of exposure: Oral
 Test: NOAEL
 Result: 227 mg/kg bw/day

Product/substance: Disodium metasilicate
 Species: Mouse
 Route of exposure: Oral
 Test: NOAEL
 Result: 260 mg/kg bw/day

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

We have not carried out any animal testing for this product. Any ATE figures quoted below are from toxicity classifications that have been carried out using ATE (Acute Toxicity Estimate) calculation method, using LD50 or ATE figures provided by the raw material manufacturer.

Product/substance: 2-aminoethanol;ethanolamine
 Species: Daphnia
 Duration: 48 hours
 Test: EC50
 Result: 65 mg/L

Product/substance: 2-aminoethanol;ethanolamine
 Species: Algae
 Duration: 72 hours
 Test: ErC50
 Result: 2.5 mg/L

Product/substance	Disodium metasilicate
Species:	Fish, Brachydanio rerio
Duration:	96 hours
Test:	LC50
Result:	210 mg/L
Product/substance	Disodium metasilicate
Species:	Daphnia, Daphnia magna
Duration:	48 hours
Test:	EC50
Result:	1700 mg/L
Product/substance	Disodium metasilicate
Species:	Algae, Scenedesmus subspicatus
Duration:	72 hours
Test:	EC50
Result:	207 mg/L
Product/substance	Disodium metasilicate
Species:	Algae, Scenedesmus subspicatus
Duration:	72 hours
Test:	EC50
Result:	> 345.4 mg/L
Product/substance	2-butoxyethanol
Test method:	OECD 203
Species:	Fish, Oncorhynchus mykiss
Duration:	96 hours
Test:	LC50
Result:	1474 mg/L
Product/substance	2-butoxyethanol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	1550 mg/L
Product/substance	sodium hydroxide;caustic soda
Species:	Fish, Brachydanio rerio
Duration:	96 hours
Test:	LC50
Result:	125 mg/L
Product/substance	sodium hydroxide;caustic soda
Species:	Daphnia, Ceriodaphnia dubia
Duration:	48 hours
Test:	EC50
Result:	40.4 mg/L
Product/substance	sodium hydroxide;caustic soda
Species:	Bacteria, Photobacterium phosphoreum
Duration:	15 minutes
Result:	22 mg/L
Product/substance	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts
Species:	Fish
Test:	LC50
Result:	1.1 mg/L
Product/substance	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Species: Daphnia
 Test: EC50
 Result: 1.9 mg/L

Product/substance 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts
 Species: Algae
 Test: ErC50
 Result: 2.4 mg/L

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents as retained and amended in UK law. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

Product/substance 2-aminoethanol;ethanolamine
 Conclusion: No potential for bioaccumulation

Product/substance 2-butoxyethanol
 LogKow: 0.81
 Conclusion: Bioaccumulation is not expected

Product/substance sodium hydroxide;caustic soda
 LogKow: -3,88
 Conclusion: -

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 8 – Corrosive

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

Not applicable.

Specific labelling



Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es) Label: 8	14.4 PG*	14.5 Env**	Other informatio n: Limited quantities: 5
ADR	UN1760	CORROSIVE LIQUID, N.O.S. (2-aminoethanol;ethanolamine, Disodium	Transport hazard class: 8 Label: 8	III	No	

According to REACH Regulation (EC) No 1907/2006, as retained and amended by SI 2019/758 and SI 2020/1577

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
		metasilicate)	Classification code: C9 			L Tunnel restriction code: (E) See below for additional information .
IMDG	UN1760	CORROSIVE LIQUID, N.O.S. (2-aminoethanol;ethanolamine, Disodium metasilicate)	Transport hazard class: 8 Label: 8 Classification code: C9 	III	No	Limited quantities: 5 L EmS: F-A S- B See below for additional information .
IATA	UN1760	CORROSIVE LIQUID, N.O.S. (2-aminoethanol;ethanolamine, Disodium metasilicate)	Transport hazard class: 8 Label: 8 Classification code: C9 	III	No	See below for additional information .

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

Hazchem Code: 2X

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

Not applicable.

Labelling of contents according to Detergents Regulation (EC) No 648/2004 as retained and amended in UK law
< 5%

- Amphoteric surfactants
- Non-ionic surfactants

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents as retained and amended in UK law. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Regulation (EC) No 648/2004 on detergents as retained and amended in UK law.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H290, May be corrosive to metals.

H302, Harmful if swallowed.

H312, Harmful in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H412, Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

[The safety data sheet is validated by EcoOnline](#)

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en