

Product Hand Sanitizer
 Revision date 27 May 2022
 Revision 3



Safety Data Sheet (SDS)

according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier

Product name	Hand Sanitizer
Product no.	808
Synonyms, Trade names	No information available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Hand Sanitiser.
Uses advised against	Any other purpose.

1.3 Details of the supplier of the safety data sheet

Supplier	Kitchenmaster NI Ltd 11 Comber Road Belfast BT8 8AN United Kingdom Tel: 028 90814777 sales@kitchenmaster-ni.com
Contact person	

1.4 Emergency telephone number

Emergency telephone	Emergency Telephone Number: 028 9081 4777 08:30 - 17:00 Monday to Thursday 08:30 - 16:30 Friday
---------------------	---

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)	
Physical and chemical hazards	Flam. Liq 2- H225
Human health	Not classified
Environment	Not classified

2.2 Label elements

Contains	Not applicable
----------	----------------

Label in accordance with (EC) no. 1272/2008



Signal word	Danger
-------------	--------

Hazard statements	H225 Highly flammable liquid and vapour.
-------------------	--

Precautionary statements

Prevention

P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking.
 P243 Take precautionary measures against static discharge.
 P280 Wear protective gloves/ protective clothing/eye protection/face protection.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/ shower.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

2.3 Other hazards

None known.

Section 3: Composition/identification of ingredients**3.1 Substance**

Not applicable.

3.2 Mixtures

Name	Product identifier	Reg. EU 1272/2008	%
Ethanol	CAS-No.: 64-17-5 EC No.: 200-578-6 REACH Reg No.: 01-2119457610-43	Eye Irrit.2A - H319, Flam. Liq 2- H225	40-50%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Section 4: First aid measures**4.1 Description of first aid measures**

General information	Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem.
Inhalation	If this product is inhaled and symptoms occur, move the exposed person to fresh air promptly. Seek medical attention if symptoms persist.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Rinse mouth out and then drink plenty of water. Get medical attention if any discomfort continues.
Skin contact	Wash off with soap and water. No special treatment normally needed. Get medical attention if irritation develops and persists. Launder contaminated clothing before reuse.
Eye contact	If this product contacts the eyes, gently flush eyes with lukewarm water for at least fifteen (15) minutes, lifting the upper and lower eyelids occasionally. Remove contact lenses if worn. Seek medical attention if irritation persists. Avoid contaminating unaffected eye.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms noted.
Ingestion	May cause discomfort if swallowed.
Skin contact	No specific symptoms noted.
Eye contact	May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
-------------------------------	------------------------

Section 5: Fire-fighting measures**5.1 Extinguishing media**

Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	High volume water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	During fire, toxic gases (CO, CO ₂) are formed.
Unusual fire & explosion hazards	Flammable vapours may spread to sources of ignition or accumulate in confined spaces.
Specific hazards	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂). In the event of damage to packaging, floors may become slippery, avoid falls.

5.3 Advice for firefighters

Special fire fighting procedures	If possible, fight fire from protected position. Ventilate closed spaces before entering them. Keep up-wind to avoid fumes. Avoid breathing fire vapours. Containers close to fire should be removed immediately or cooled with water if safe to do so.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. In case of inadequate ventilation, use respiratory protection. Do not touch or walk through spilled material. If necessary evacuate surrounding areas.
For emergency responders	Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions

Environmental precautions	Do not discharge onto the ground or into water courses.
---------------------------	---

6.3 Methods and material for containment and cleaning up

Spill clean up methods	Stop leak if possible without risk. When dealing with a spillage, wear necessary protective equipment. Eliminate all ignition sources. Absorb spillage with non-combustible, inert absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with a spillage. Floors may become slippery, avoid falls.
------------------------	---

6.4 Reference to other sections

Reference to other sections	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.
-----------------------------	--

Section 7: Handling and storage**7.1 Precautions for safe handling**

Handling	Read and follow manufacturer's recommendations. Use proper personal protection when handling (refer to Section 8). Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Wash thoroughly after handling.
----------	--

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions	Keep upright, locked up and out of reach of children. Keep the product in its original container. Store in cool dry areas away from direct sunlight or sources of ignition.
Storage class	Flammable liquid storage.

7.3 Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
Usage description	Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
ethanol	OEL			1000 ppm		
ethanol	WEL	1000 ppm	1920 mg/m ³			

Ingredient comments

Ireland, Occupational Exposure Limits 2020.
Workplace Exposure Limits Guidance Note EH40/2005.

8.2 Exposure Controls

Protective equipment



Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
Where necessary use lighting and electrical equipment designed for use in atmospheres where flammable vapours are present, and which can direct static electricity by grounding equipment.

Respiratory equipment

Respiratory protection not required in normal conditions. In case of large scale spill in confined area: Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Recommended: Respirator with combination filter for organic vapour/particulate (EN 141). ABEK (EN 14387). Consult manufacturer for specific advice.

Hand protection

Not normally required, however helpful for prolonged or repeated contact. (Suggested suitable materials for longer, direct contact or splash contact) Suggested material: Butyl-rubber. Layer thickness: 0.7 mm. Breakthrough time: >480 minutes.
Nitrile rubber. Layer thickness: > 1 mm. Breakthrough time: >480 minutes. Consult manufacturer for advice. Recommended properties: Impervious gloves in accordance with standard EN374.

Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Eye protection

If there is a risk of eye contact: Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU). Safety glasses with side shields.

Other protection

Protective clothing not required for normal use of the product. Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected clothing must satisfy the European norm standard EN 943.

Hygiene measures

Observe normal hygiene standards. When using do not eat, drink or smoke.

Process conditions

Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Non-viscous liquid.
Colour	Aquamarine. Clear.
Odour	Alcohol.
Odour threshold - lower	No information available as testing has not been completed.
Odour threshold - upper	No information available as testing has not been completed.
pH-Value, Conc. Solution	5 - 7
pH-Value, Diluted solution	Not applicable as the product is a concentrated solution.
Melting point	-114 °C (Ethanol 100% literature data)

Initial boiling point and boiling range	The boiling point of ethanol at normal atmospheric pressure is 351K (78.5C). (Ethanol 100% literature data)
Flash point	24.00 °C
Evaporation rate	No information available as testing has not been completed.
Flammability state	Highly flammable liquid and vapor.
Flammability limit - lower(%)	No information available as testing has not been completed.
Flammability limit - upper(%)	No information available as testing has not been completed.
Vapour pressure	The vapour pressure of ethanol at 19.6 °C is 57.26 hPa.(Ethanol 100% literature data)
Vapour density (air=1)	No information available as testing has not been completed.
Relative density	No information available as testing has not been completed.
Bulk density	Not applicable as the product is a liquid.
Solubility	Soluble in water.
Decomposition temperature	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	The logKow for ethanol is -0.35 at 24 °C. (Ethanol 100% literature data)
Auto ignition temperature (°C)	368.8 °C (Ethanol 100% literature data)
Viscosity	1.17 mPa · s (dynamic) (Ethanol 100% literature data)
Explosive properties	Not classified as explosive.
Oxidising properties	The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight	Not applicable as the product is a mixture.
Volatile organic compound	No information available as testing has not been completed.
Other information	None noted.

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity	No specific reactivity hazards associated with this product.
------------	--

10.2 Chemical stability

Stability	Stable under normal temperature conditions and recommended use
-----------	--

10.3 Possibility of hazardous reactions

Hazardous reactions	For information on hazardous reactions see section 10.1.
Hazardous polymerisation	Hazardous polymerisation is not expected to occur under normal temperatures and pressures.
Polymerisation description	Unknown.

10.4 Conditions to Avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.
---------------------	---

10.5 Incompatible materials

Materials to avoid

Keep away from incompatibles such as oxidizing agents, acids, alkalis.

10.6 Hazardous decomposition productsHazardous decomposition products Fire creates: Toxic gases/vapours/fumes of carbon monoxide (CO), and carbon dioxide (CO₂).**Section 11: Toxicological information****11.1 Information on toxicological effects**

Toxicological information	No toxicological information for the overall finished product.
Acute toxicity (Oral LD50)	No information available as testing has not been completed.
Acute toxicity (Dermal LD50)	No information available as testing has not been completed.
Acute toxicity (Inhalation LD50)	No information available as testing has not been completed.
Serious eye damage/irritation	May cause eye irritation.
Skin corrosion/irritation	The product is not classified as a skin corrosion/irritation hazard.
Respiratory sensitisation	The product is not classified as a respiratory hazard.
Skin sensitisation	The product is not classified as a skin sensitisation hazard.
Germ cell mutagenicity	The product is not classified as a mutagen.
Carcinogenicity	The product is not classified as a carcinogen hazard.
Specific target organ toxicity - Single exposure:	
STOT - Single exposure	The product is not classified as a single exposure specific target organ toxin.
Specific target organ toxicity - Repeated exposure:	
STOT - Repeated exposure	The product is not classified as a repeat exposure specific target organ toxin.
Inhalation	No specific symptoms noted.
Ingestion	May cause discomfort if swallowed.
Skin contact	No specific symptoms noted.
Eye contact	May cause temporary eye irritation.
Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
Routes of entry	Eyes, skin, ingestion or inhalation.
Target organs	Eyes, skin, digestive system, respiratory system, central nervous system.
Aspiration hazards:	The product is not classified as an aspiration hazard.
Reproductive toxicity:	The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
Ethanol	>2000.00mg/kg Rat	>2000.00mg/kg Rabbit	>20.00mg/l (vapours) Rat 4 Hours
Benzyl-C12-14-alkyldimethylammonium chlorides	379.50mg/kg Rat	3412.00mg/kg Rabbit	

Section 12: Ecological information**12.1 Toxicity**

Acute toxicity - Fish	No information available as testing has not been completed.
Acute toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Acute toxicity - Aquatic plants	No information available as testing has not been completed.
Acute toxicity - Microorganisms	No information available as testing has not been completed.
Chronic toxicity - Fish	No information available as testing has not been completed.
Chronic toxicity - Aquatic invertebrates	No information available as testing has not been completed.
Chronic toxicity - Aquatic plants	No information available as testing has not been completed.
Chronic toxicity - Microorganisms	No information available as testing has not been completed.
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Eco toxicological information	Not classified as dangerous for the environment according to the criteria of Regulation (EC)

No 1272/2008.

12.2 Persistence and degradability

Degradability	The product is readily biodegradable.
Biological oxygen demand	No information available as testing has not been completed.
Chemical oxygen demand	No information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Bioaccumulation factor	No information available as testing has not been completed.
Partition coefficient; n-Octanol/Water	The logKow for ethanol is -0.35 at 24°C. (Ethanol 100% literature data)

12.4 Mobility in soil

Mobility	The product is soluble in water.
----------	----------------------------------

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Other adverse effects

Other adverse effects	None known.
-----------------------	-------------

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
Ethanol	LC50 96 Hours 15300.00mg/l Pimephales promelas (Fat-head Minnow)	EC50 48 Hours >10000.00mg/l Daphnia magna	
Benzyl-C12-14-alkyldimethylammonium chlorides	LC50 0.52mg/l Freshwater Fish	EC50 0.02mg/l Daphnia magna	

Section 13: Disposal considerations

Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
------------------	--

13.1 Waste treatment methods

Disposal methods	Dispose of waste and residues in accordance with local authority requirements.
------------------	--

Section 14: Transport information**14.1 UN number**

UN no. (ADR)	UN1170
UN no. (IMDG)	UN1170
UN no. (IATA)	UN1170

14.2 UN proper shipping name

ADR proper shipping name	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
IMDG proper shipping name	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
IATA proper shipping name	ETHANOL

14.3 Transport hazard class(es)

ADR class	3
IMDG class	3
IATA class	3

Transport labels

**14.4 Packing group**

ADR/RID/ADN packing group	II
IMDG packing group	II
IATA packing group	II

14.5 Environmental hazards

ADR	No
IMDG	No
IATA	No

14.6 Special precautions for user

EMS	F-E, S-D
Emergency action code	A3 A58 A180
Hazard no. (ADR)	33
Tunnel restriction code	(D/E)

14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code

Not applicable.

Section 15: Regulatory information**15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture**

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th May 2010 amending regulation (EC) No 1907/2006.
Approved code of practice	Workplace Exposure Limits Guidance Note EH40/2005. 2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
Chemical safety assessment	No chemical safety assessment has been carried out.

Section 16: Other information

General information	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
Revision comments	This is a third issue. [3]Information updated. [5]Information updated. [8]Information updated. [9]Information updated. [10]Information updated. [11]Information updated. [12]Information updated. [14]Information updated. [15]Information updated.
Revision date	27 May 2020
Supersedes date	17 July 2017
Revision	3
Safety data sheet status	Approved.

Hazard statements in full

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.