



11 Comber Road, Carryduff, BELFAST, BT8 8AN
Tel: 028 9081 4777 Fax: 028 9081 2881
Website: www.kitchenmaster-ni.com Email: sales@kitchenmaster-ni.com

TECHNICAL SPECIFICATION

TRUCK CLEAN

A newly developed product specially formulated for the removal of protective wax coatings on new cars. Due to its advanced formulation it effectively removes heavy-duty traffic film from all types of vehicles fast and effectively. It cuts through the toughest of grime and dries quickly to leave surfaces sparkling clean. Developed from a blend of amphoteric surfactants, non-ionic surfactants, sequestering agents, silicates, foam boosters, foam stabilisers, hydrotrope, corrosion inhibitors, non-caustic alkalis, solvents and water-soluble dyes.

Features include:

- Suitable for use in all cleaning equipment.
- Removes protective wax layer sprayed onto new cars.
- Solvents present ensures fast, even drying.
- Fast drying prevents watermarks and therefore reduces need for polishing.
- All surfactants used are biodegradable and phosphate free.
- Special blend of emulsifies traffic film, grease and oil from vehicles.
- Silicates present leave windows sparkling clean.
- Can be used for removing diesel & soil stains and spills from service station forecourts and pumps.
- Suitable for cleaning all vehicle types, including tractor units, tankers and refrigerated vehicles.

PROPERTIES:

Appearance @ 20°C
Odour
pH (neat)
Specific Gravity @ 20°C
Flammability

SPECIFICATION:

Clear, colourless, non viscous liquid
Characteristic
>13.5
1.030 +/- 0.005
Non-flammable

DIRECTIONS FOR USE:

- For fixed area and automatic vehicle washes, use at a concentration of between 1:200-1:65.
- For steam cleaning / hot pressure wash / cool pressure wash, use at a concentration of between 1:200-1:50. Apply at low pressure (50psi).
- Do not allow vehicle to dry.
- Sponge the vehicle to loosen soils and traffic film. Clean with plenty of clean water at high pressure.
- Use at a concentration of between 1:40 -1:10 for cleaning forecourts and pumps etc.

STORAGE:

Store in original container and protect from extremes of temperature. Do not store in direct sunlight nor allow the product to freeze. Shelf life (in unopened original container) is a minimum of 18 months.

SAFETY ADVICE:

Under the new GHS Standard this product is classified as Corrosive. Please refer to section 2.2 of the Safety Data Sheet for more information.

PACK SIZE:

25L drums (32 per pallet)
200L drums (4 per pallet)

Order Code: INDTRUCK-25L
Order Code: INDTRUCK-200L