

11 Comber Road, Carryduff, BELFAST, BT8 8AN Tel: 028 9081 4777 Fax: 028 9081 2881

Website: www.kitchenmaster-ni.com Email: sales@kitchenmaster-ni.com

# TECHNICAL SPECIFICATION VEHICLE CLEANER

A high performance advanced product, specially formulated for the removal of heavy duty traffic film from all types of vehicles. Developed from a blend of anionic, non-ionic and amphoteric surfactants, silicates, sequestering agents, hydrotrope, caustic and non-caustic alkalis, corrosion inhibitors and water soluble dyes.

# Features include:

- Suitable for use in all cleaning equipment.
- All surfactants used are biodegradable and phosphate free.
- Emulsifies traffic film, grease and oil from vehicles.
- Silicates present leave windows sparkling clean.
- Can be used for removing diesel & oil stains and skills from service station forecourts and pumps.
- Suitable for cleaning all vehicle types, including tractor units, tankers and refrigerated vehicles.

# **PROPERTIES:**

Appearance @ 20°C
Odour
pH (neat)
Specific Gravity @ 20°C
Flammability

#### **SPECIFICATION:**

Red, low viscosity liquid Characteristic >13.5 1.034 +/- 0.005 Non-flammable

Order Code: INDSTDVEH-25L

Order Code: INDSTDVEH-200L

#### **DIRECTIONS FOR USE:**

- For fixed area and automatic vehicle washes, use at a concentration of between 1:200-1:65.
- For steam cleaning / hot pressure wash / cool pressure wash, use at a concentration of between 1:200-1:50. Apply at low pressure (50psi).
- Do not allow vehicle to dry, quickly remove loosened soils and traffic film with plenty of clean water at high pressure.
- Use at a concentration of between 1:40-1:10 for cleaning forecourts and pumps etc.

## STORAGE:

Store in original container and protect from extremes of temperature. Do not store in direct sunlight nor allow the product to freeze. Shelf life (in unopened original container) is a minimum of 18 months.

## **SAFETY ADVICE:**

Under the new GHS Standard this product is classified as Corrosive. Please refer to section 2.2 of the Safety Data Sheet for more information.

#### **PACK SIZE:**

25L drums (32 per pallet) 200L drums (4 per pallet)