



Safety data sheet according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 604 - Heavy Duty Degreaser
- **Product Code:** HSC604
- **Registration number** Mixture
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category** PC35 Washing and cleaning products (including solvent based products)
- **Application of the substance / the mixture** Cleaning agent/ Cleaner
- **Uses advised against** The product is strictly intended for professional use only.
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
Kitchenmaster Group Ltd
11 Comber Road
Carryduff
Belfast, BT8 8AN

Tel: 028 9081 4777
Email: sales@kitchenmaster-ni.com
- **Further information obtainable from:** Product safety department.
- **1.4 Emergency telephone number:**
Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

* SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to GB-CLP**
Met. Corr.1 H290 May be corrosive to metals.
Skin Corr. 1C H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
- **2.2 Label elements**
- **Labelling according to GB-CLP** The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Alcohols, C12 -13- branched and linear, ethoxylated [1 - 2.5 moles ethoxylated]
Potassium hydroxide
Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl)

(Contd. on page 2)



Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 1)

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulations.

· 2.3 Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

* SECTION 3: Composition/information on ingredients

· 3.2 Mixtures**· Description:** An aqueous solution of the substances listed below with multifunctional additives.**· Dangerous components:**

CAS: 160901-19-9 NLP: 500-457-0 Reg.nr.: 01-2119490233-42-XXXX	Alcohols, C12 -13- branched and linear, ethoxylated [1 - 2.5 moles ethoxylated] ☠ Eye Dam. 1, H318; ☠ Acute Tox. 4, H302; Aquatic Chronic 3, H412 ATE: LD50 oral: 500 mg/kg	2.5 – < 3%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-XXXX	Isopropyl alcohol ☠ Flam. Liq. 2, H225; ☠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5 – < 10%
CAS: 68155-07-7 Reg.nr.: 01-2119490100-53-XXXX	Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ☠ Eye Dam. 1, H318; ☠ Aquatic Chronic 2, H411; ☠ Skin Irrit. 2, H315	1 – < 2.5%

(Contd. on page 3)

— GB —



Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 2)

CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36-XXXX	2-butoxyethanol ⚠ Acute Tox. 3, H331; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg LC50/4 h inhalative: 3 mg/l	1 – 2.5%
CAS: 1310-58-3 EINECS: 215-181-3 Index number: 019-002-00-8 Reg.nr.: 01-2119487136-33-XXXX	Potassium hydroxide ⚠ Skin Corr. 1A, H314; ⚠ Acute Tox. 4, H302 Specific concentration limits: Skin Corr. 1A; H314: $C \geq 5\%$ Skin Corr. 1B; H314: $2\% \leq C < 5\%$ Skin Irrit. 2; H315: $0.5\% \leq C < 2\%$ Eye Irrit. 2; H319: $0.5\% \leq C < 2\%$	1 – < 2%
CAS: 1300-72-7 EINECS: 215-090-9	Sodium xylenesulphonate ⚠ Eye Irrit. 2, H319	1 – 2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

· **After inhalation:**

In case of inhalation:

- Provide fresh air.
- In case of breathing difficulties administer oxygen.
- No mouth-to-mouth or mouth-to-nose resuscitation. Use respiratory bag or oxygen resuscitation apparatus.
- Do not leave patient unattended.

If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

· **After skin contact:**

Immediately rinse with water.

If skin irritation continues, consult a doctor.

Chemical burns must be treated promptly by a physician.

· **After eye contact:**

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Wash mouth out with water

Do not induce vomiting; call for medical help immediately.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

· **Information for doctor:**

Inhalation of an aerosol of this substance may cause lung oedema.

Treat symptomatically and supportively.

· **4.2 Most important symptoms and effects, both acute and delayed** Corrosive damage to gastro-intestinal tract.

· **Hazards** Danger of gastric perforation.

(Contd. on page 4)



Safety data sheet
according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.
-

* **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
 - **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
 - **For safety reasons unsuitable extinguishing agents:** Water with full jet
 - **5.2 Special hazards arising from the substance or mixture**
Corrosive liquid.
May react with metals, releasing hydrogen.
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)
Silicon compounds
Sulphur Oxides (SO_x)
 - **5.3 Advice for firefighters**
 - **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
 - **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.
-

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Particular danger of slipping on leaked/spilled product.
 - **6.2 Environmental precautions:**
Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
 - **6.3 Methods and material for containment and cleaning up:**
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Contaminated absorbent material may pose the same hazard as the spilt product.
Ensure adequate ventilation.
 - **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
-

GB

(Contd. on page 5)



Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 4)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.

Safety showers and eye wash facilities should be available at the work area.

· Information about fire - and explosion protection: Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Store only in the original receptacle.

· Information about storage in one common storage facility: Do not store together with acids.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from frost.

· Storage class: 8 A

· 7.3 Specific end use(s) No further relevant information available.

* SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 Isopropyl alcohol

WEL Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

CAS: 111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm

Long-term value: 123 mg/m³, 25 ppm

Sk, BMGV

CAS: 1310-58-3 Potassium hydroxide

WEL Short-term value: 2 mg/m³

· DNELs

CAS: 160901-19-9 Alcohols, C12 -13- branched and linear, ethoxylated [1 - 2.5 moles ethoxylated]

Oral Long-term systemic effects 1.67 mg/kg bw/day (general population)

Dermal Long-term systemic effects 83.3 mg/kg bw/day (general population)

233 mg/kg bw/day (worker)

Inhalative Long-term systemic effects 4.36 mg/m³ (general population)

24.5 mg/m³ (worker)

(Contd. on page 6)



Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 5)

CAS: 67-63-0 Isopropyl alcohol		
Oral	Long-term systemic effects	26 mg/kg bw/day (general population)
	Short-term systemic effects	51 mg/kg bw/day (general population)
Dermal	Long-term systemic effects	319 mg/kg bw/day (general population)
		888 mg/kg bw/day (worker)
Inhalative	Long-term systemic effects	89 mg/m ³ (general population)
		500 mg/m ³ (worker)
	Short-term systemic effects	178 mg/m ³ (general population)
		1,000 mg/m ³ (worker)
CAS: 68155-07-7 Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl)		
Oral	Long-term systemic effects	1.17 mg/kg bw/day (general population)
Dermal	Long-term systemic effects	89.3 µg/kg bw/day (general population)
		750 µg/kg bw/day (worker)
Inhalative	Long-term systemic effects	2.03 mg/m ³ (general population)
		11.5 mg/m ³ (worker)
CAS: 111-76-2 2-butoxyethanol		
Oral	Long-term systemic effects	6.3 mg/kg bw/day (general population)
	Short-term systemic effects	26.7 mg/kg bw/day (general population)
Inhalative	Long-term systemic effects	59 mg/m ³ (general population)
		98 mg/m ³ (worker)
	Short-term systemic effects	426 mg/m ³ (general population)
		1,091 mg/m ³ (worker)
	Short-term local effects	147 mg/m ³ (general population)
		246 mg/m ³ (worker)
CAS: 1310-58-3 Potassium hydroxide		
Inhalative	Long-term local effects	1 mg/m ³ (general population)
		1 mg/m ³ (worker)
· PNECs		
CAS: 160901-19-9 Alcohols, C12 -13- branched and linear, ethoxylated [1 - 2.5 moles ethoxylated]		
Freshwater		1.23 µg/L
Freshwater - Intermittent releases		1.795 µg/L
Marine water		123 ng/L
Marine Water - Intermittent releases		179 ng/L
Sewage Treatment Plant		200 µg/L
Sediment (freshwater)		29 µg/kg
Sediment (marine water)		2.9 µg/kg
Soil		8.6 µg/kg

(Contd. on page 7)



Safety data sheet
according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 6)

CAS: 68155-07-7 Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl)	
Freshwater	7 µg/L
Freshwater - Intermittent releases	24 µg/L
Marine water	700 ng/L
Marine Water - Intermittent releases	2.4 µg/L
Sewage Treatment Plant	830 mg/L
Sediment (freshwater)	230 µg/kg
Sediment (marine water)	23 µg/kg
Soil	32 mg/kg
CAS: 111-76-2 2-butoxyethanol	
Freshwater	8.8 mg/L
Freshwater - Intermittent releases	26.4 mg/L
Marine water	880 µg/L
Sewage Treatment Plant	463 mg/L
Sediment (freshwater)	34.6 mg/kg
Sediment (marine water)	3.46 mg/kg
Soil	2.33 mg/kg
Secondary poisoning	20 mg/kg food
· Ingredients with biological limit values:	
CAS: 111-76-2 2-butoxyethanol	
BMGV	240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Take note of assigned Workplace Exposure Limits.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Ensure that eyewash stations and safety showers are close to the workstation location.

Do not eat or drink while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

· **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 8)



Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 7)

· Hand protection

Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Tightly sealed goggles conforming to EN166.



Face shield/visor.

Use equipment tested and approved under appropriate government standards such as EN166 (EU) or NIOSH (US)

Use visor in combination with goggles.

· Body protection:

Protective work clothing

Do not get on skin or clothing. Wear clothing and footwear that cannot be penetrated by the product. Suitable protective equipment may include: Chemical resistant boots, Chemical resistant apron, Full chemical protective suit with a hood, Chemical protective suit consisting of a jacket and trousers. The jacket should be buttoned up to the neck, sleeves sealed at the gloves, and trouser legs worn outside the boots. These precautions are required to prevent the clothing from accidentally trapping product against the skin.

· Environmental exposure controls Do not allow to enter drains, sewers or watercourses.**· Risk management measures** The operators shall be instructed adequately.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Physical state**

Liquid

· Colour:

Colourless

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

(Contd. on page 9)

— GB —



Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 8)

· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	> 70 °C
· Decomposition temperature:	Not determined.
· pH at 20 °C	> 13
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.02 – 1.03 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Liquid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not self-igniting.
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· VOC (EC)	4.89 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes	
· Explosives	Not applicable
· Flammable gases	Not applicable
· Aerosols	Not applicable
· Oxidising gases	Not applicable
· Gases under pressure	Not applicable
· Flammable liquids	Not applicable
· Flammable solids	Not applicable
· Self-reactive substances and mixtures	Not applicable
· Pyrophoric liquids	Not applicable
· Pyrophoric solids	Not applicable
· Self-heating substances and mixtures	Not applicable
· Substances and mixtures, which emit flammable gases in contact with water	Not applicable
· Oxidising liquids	Not applicable
· Oxidising solids	Not applicable
· Organic peroxides	Not applicable

(Contd. on page 10)



Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 9)

- **Corrosive to metals**
- **Desensitised explosives**

May be corrosive to metals.
Not applicable

* SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
 - Exothermic reaction with acids.
 - Reacts with light alloys to form hydrogen.
- **10.4 Conditions to avoid** Heat and static discharge.
- **10.5 Incompatible materials:**
 - Strong acids.
 - Light metals and their alloys.
- **10.6 Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide
 - Nitrogen oxides (NO_x)
 - Silicon compounds
 - Sulphur oxides (SO_x)

* SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	8,072.2 mg/kg
Inhalative	LC50/4 h	153.93 mg/l (ATE)

CAS: 67-63-0 Isopropyl alcohol

Oral	LD50	> 2,000 mg/kg (rat)
------	------	---------------------

CAS: 68155-07-7 Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl)

Oral	LD50	> 2,000 mg/kg (rat)
Dermal	LD50	> 2,000 mg/kg (rabbit)

CAS: 111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE)
Dermal	LD50	3,000 mg/kg (rabbit)
Inhalative	LC50/4 h	3 mg/l (ATE)
		3 mg/l (rat)

CAS: 1310-58-3 Potassium hydroxide

Oral	LD50	333 mg/kg (rat)
------	------	-----------------

(Contd. on page 11)



Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 10)

CAS: 1300-72-7 Sodium xylenesulphonate

Oral	LD50	> 2,000 mg/kg (rat)
Dermal	LD50	> 2,000 mg/kg (rabbit)

· Primary irritant effect:**· Skin corrosion/irritation**

Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.**· Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**· Germ cell mutagenicity** Based on available data, the classification criteria are not met.**· Carcinogenicity** Based on available data, the classification criteria are not met.**· Reproductive toxicity** Based on available data, the classification criteria are not met.**· STOT-single exposure** Based on available data, the classification criteria are not met.**· STOT-repeated exposure** Based on available data, the classification criteria are not met.**· Aspiration hazard** Based on available data, the classification criteria are not met.**· Additional toxicological information:**

ROUTES OF EXPOSURE: Serious local effects by all routes of exposure.

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of oesophagus and stomach.

Inhalation may cause lung oedema, but only after initial corrosive effects on eyes and/or airways have become manifest. The symptoms of lung oedema often do not become manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation are therefore essential. Immediate administration of an appropriate inhalation therapy by a doctor or a person authorized by him/her, should be considered.

· 11.2 Information on other hazards**· Endocrine disrupting properties**

None of the ingredients are listed.

SECTION 12: Ecological information

· 12.1 Toxicity**· Aquatic toxicity:****CAS: 67-63-0 Isopropyl alcohol**

EC50 (96 h) > 10,000 mg/l (Bacteria)

CAS: 68155-07-7 Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl)

EC50 (72 h) 3.9 mg/l (algae)

CAS: 1300-72-7 Sodium xylenesulphonate

EC50 (96 h) > 200 mg/l (Bacteria)

· 12.2 Persistence and degradability The organic portion of the product is biodegradable.**· 12.3 Bioaccumulative potential** Contains components with the potential to bioaccumulate.**· 12.4 Mobility in soil** No further relevant information available.**· 12.5 Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**· 12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

(Contd. on page 12)



Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 11)

· 12.7 Other adverse effects**· Additional ecological information:****· General notes:**

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods**· Recommendation**

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· Uncleaned packaging:**· Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Disposal must be made according to official regulations.

Container remains hazardous when empty. Continue to observe all precautions.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

· Recommended cleansing agents: Large quantities of water

SECTION 14: Transport information

· 14.1 UN number or ID number**· ADR/RID/ADN, IMDG, IATA**

UN3266

· 14.2 UN proper shipping name**· ADR/RID/ADN**

UN3266 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (POTASSIUM HYDROXIDE)

· IMDG, IATA

CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (POTASSIUM HYDROXIDE)

(Contd. on page 13)

— GB —



Safety data sheet
according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 12)

· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
	
· Class	8 (C5) Corrosive substances.
· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Hazard identification number (Kemler code):	80
· Hazchem Code:	2X
· EMS Number:	F-A,S-B
· Segregation groups	(SGG18) Alkalies
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L

(Contd. on page 14)



Safety data sheet
according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 13)

· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3266 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (POTASSIUM HYDROXIDE), 8, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· Regulated explosives precursors		
None of the ingredients are listed.		
· Regulated poisons		
None of the ingredients are listed.		
· Reportable explosives precursors		
None of the ingredients are listed.		
· Reportable poisons		
CAS: 1310-58-3	Potassium hydroxide	17% of total caustic alkalinity

- **Control Of Major Accident Hazards Regulations 2015 (COMAH)**
- **Named dangerous substances - ANNEX I** None of the ingredients are listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

- **Training hints**

This product should only be handled by workers who have received sufficient training in the safe handling and use of chemical products.

(Contd. on page 15)



Safety data sheet
according to UK REACH (SI 2020/1577) as amended

Printing date 26.03.2025

Version number 2 (replaces version 1)

Revision: 26.03.2025

Trade name: 604 - Heavy Duty Degreaser

(Contd. of page 14)

· **Department issuing SDS:** Product safety department.

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquids – Category 2

Met. Corr. 1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**