SAFETY DATA SHEET

Reload No 6 Glass & Stainless Steel Cleaner Concentrate

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Reload No 6 Glass & Stainless Steel Cleaner Concentrate

Product no.

REAQUAGLASS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning agent
Restricted to professional users.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Kitchenmaster NI Ltd
11 Comber Road,
BT8 8AN Belfast
United Kingdom
028 9081477 02890812881
sales@kitchenmaster-ni.com

E-mail

sales@kitchenmaster-ni.com

Revision

24/04/2024

SDS Version

1.0

1.4. Emergency telephone number

In an emergency call 999 (24 h service). Otherwise contact your general practitioner (GP).
GP Out-of-Hours phone numbers (weekdays 6 pm - 8 am ; Saturday, Sundays and holidays 24 h) are:
Belfast HSC Trust: (North & West) 028 9074 4447 ; (South & East) 028 9079 6220
Dalriada Urgent Care (Northern Trust area): 028 2566 3500
South Eastern HSC Trust: (North Down & Ards) 028 9182 2344 : (Lisburn & Downpatrick) 028 9260 2204
Southern HSC Trust: 028 3839 9201
Western Urgent Care: 028 7186 5195

See section 4 “First aid measures”.
Emergency contact number (Kitchenmaster): +44 (0)28 9081 4777 (8.30am - 5pm, Monday - Thursday; 8.30am - 4pm Friday)

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

2.2. Label elements

Hazard pictogram(s)



Signal word
Warning

Hazard statement(s)
Flammable liquid and vapour. (H226)

Precautionary statement(s)

General
-

Prevention
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Wear eye protection/protective gloves/protective clothing. (P280)

Response
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam/powder to extinguish. (P370+P378)

Storage
Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal
Dispose of contents/container in accordance with local regulation
(P501)

Hazardous substances
None known.

Additional labelling
Not applicable.

Labelling of contents according to Detergents Regulation (EC) No 648/2004
< 5%
· Anionic surfactants
· Perfumes

2.3. Other hazards

Additional warnings
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH: 01-2119457610-43-XXXX Index No.: 603-002-00-5	15-25%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 (SCL: 50.00 %)	
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0 REACH: 01-2119475108-36-XXXX Index No.: 603-014-00-0	1-3%	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]
Sodium (xylenes and 4-ethylbenzene)sulfonates	CAS No.: EC No.: 701-037-1 REACH: 01-2119513350-56-XXXX Index No.:	1-3%	Eye Irrit. 2, H319	
2-methylpropan-2-ol	CAS No.: 75-65-0 EC No.: 200-889-7 REACH: 01-2119444321-51-XXXX	0.01-0.09%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Acute Tox. 4, H332	

Index No.: 603-005-00-1	STOT SE 3, H335 STOT SE 3, H336

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.
In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

None known.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.
Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.
Use explosion-proof [electrical/lighting/ventilating] equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Take action to prevent static discharges.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

No specific requirements

Incompatible materials

Acids
Strong oxidising agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol
Long term exposure limit (8 hours) (ppm): 1000
Long term exposure limit (8 hours) (mg/m^3): 1920

2-butoxyethanol
Long term exposure limit (8 hours) (ppm): 25
Long term exposure limit (8 hours) (mg/m^3): 123
Short term exposure limit (15 minutes) (ppm): 50
Short term exposure limit (15 minutes) (mg/m^3): 246
Annotations:
BMVG = Biological Monitoring Guidance Value exists
Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-methylpropan-2-ol
Long term exposure limit (8 hours) (ppm): 100
Long term exposure limit (8 hours) (mg/m³): 308
Short term exposure limit (15 minutes) (ppm): 150
Short term exposure limit (15 minutes) (mg/m³): 462

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

2-butoxyethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	59 mg/m³
Long term – Systemic effects - Workers	Inhalation	98 mg/m³
Short term – Local effects - General population	Inhalation	147 mg/m³
Short term – Local effects - Workers	Inhalation	246 mg/m³
Short term – Systemic effects - General population	Inhalation	426 mg/m³
Short term – Systemic effects - Workers	Inhalation	1091 mg/m³
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day

Ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	206 mg/kg
Long term – Systemic effects - Workers	Dermal	343 mg/kg
Long term – Systemic effects - General population	Inhalation	114 mg/m³
Long term – Systemic effects - Workers	Inhalation	950 mg/m³
Short term – Local effects - General population	Inhalation	950 mg/m³
Short term – Local effects - Workers	Inhalation	1900 mg/m³
Long term – Systemic effects - General population	Oral	87 mg/kg

Sodium (xylenes and 4-ethylbenzene)sulfonates

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	0.048 mg/cm²
Long term – Local effects - Workers	Dermal	0.096 mg/cm²
Long term – Systemic effects - General population	Dermal	68.1 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	136.25 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	6.6 mg/m³
Long term – Systemic effects - Workers	Inhalation	26.9 mg/m³
Long term – Systemic effects - General population	Oral	3.8 mg/kg bw/day

PNEC

2-butoxyethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg
Marine water		0.88 mg/L
Marine water sediment		3.46 mg/kg
Sewage treatment plant		463 mg/L

Soil	2.33 mg/kg

Ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.96 mg/L
Freshwater sediment		3.6 mg/kg
Intermittent release		2.75 mg/L
Marine water		0.79 mg/L
Predators		0.00072 mg/kg
Sewage treatment plant		580 mg/L
Soil		0.63 mg/kg

Sodium (xylenes and 4-ethylbenzene)sulfonates

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.23 mg/L
Freshwater sediment		0.862 mg/kg
Intermittent release		2.3 mg/L
Marine water		0.023 mg/L
Marine water sediment		0.086 mg/kg
Sewage treatment plant		100 mg/L
Soil		0.037 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Work situation	Type	Class	Colour	Standards
Where risk assessment shows air-purifying respirators are appropriate.	Combination filter ABEK-P2	Class 1/2	Brown/Gray/Yellow /Green/White	EN14387



Skin protection

Work situation	Recommended	Type/Category	Standards	
In the event of a risk of splashing.	Chemical resistant clothing and shoes EN 943		EN 943	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Butyl	0,7	> 480	EN374-2, EN374-3, EN388, EN421	

Eye protection

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state
Liquid

Colour
Clear, Green

Odour / Odour threshold
Characteristic

pH
10-11

Density (g/cm^3)
0.96-0.98 (20 °C)

Kinematic viscosity
No information available as testing has not been completed.

Particle characteristics
Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)
No information available as testing has not been completed.

Softening point/range (waxes and pastes) (°C)
Does not apply to liquids.

Boiling point (°C)
No information available as testing has not been completed.

Vapour pressure
Testing not relevant or not possible due to the nature of the product.

Relative vapour density
Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)
No information available as testing has not been completed.

Data on fire and explosion hazards

Flash point (°C)
30

Flammability (°C)
The material is ignitable.

Auto-ignition temperature (°C)
No information available as testing has not been completed.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Soluble

n-octanol/water coefficient (LogKow)

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

Oxidizing properties

Testing not relevant or not possible due to nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5. Incompatible materials

Acids
Strong oxidising agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

We have not carried out any animal testing for this product. Any ATE figures quoted below are from toxicity classifications that have been carried out using ATE (Acute Toxicity Estimate) calculation method, using LD50 or ATE figures provided by the raw material manufacturer.

Acute toxicity

Product/substance	Ethanol
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	10470 mg/kg

Product/substance	Ethanol
Test method:	OECD 403
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	51 mg/L

Product/substance	Ethanol
Test method:	OECD 402
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg

Product/substance	2-butoxyethanol

Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LC50
Result:	1300 mg/kg

Product/substance	2-butoxyethanol
Species:	Guinea pig
Route of exposure:	Inhalation
Test:	LC0
Result:	>3.1 mg/L

Skin corrosion/irritation

Product/substance	Ethanol
Test method:	OECD 404
Species:	Rabbit
Result:	No adverse effect observed (Not irritating)

Serious eye damage/irritation

Product/substance	Ethanol
Test method:	OECD 405
Species:	Rabbit
Result:	Adverse effect observed (Irritating)

Product/substance	2-butoxyethanol
Test method:	OECD 405
Species:	Rabbit
Duration:	24 hours
Result:	Adverse effect observed (Irritating)

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance	Ethanol
Test method:	OECD 406
Species:	Guinea pig
Result:	No adverse effect observed (not sensitising)

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

We have not carried out any animal testing for this product. Any ATE figures quoted below are from toxicity classifications that have been carried out using ATE (Acute Toxicity Estimate) calculation method, using LD50 or ATE figures provided by the raw material manufacturer.

Product/substance	Ethanol
Species:	Daphnia, Daphnia magna
Duration:	48 hours
Test:	LC50
Result:	12340 mg/L

Product/substance	2-butoxyethanol
Test method:	OECD 203
Species:	Fish, Oncorhynchus mykiss
Duration:	96 hours
Test:	LC50
Result:	1474 mg/L

Product/substance	2-butoxyethanol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	1550 mg/L

12.2. Persistence and degradability

Product/substance	Ethanol
Result:	97%
Conclusion:	Readily biodegradable
Test:	OECD 301 B

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

Product/substance	Ethanol
LogKow:	-0.35
Conclusion:	No potential for bioaccumulation

Product/substance	2-butoxyethanol
LogKow:	0.81
Conclusion:	Bioaccumulation is not expected

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.
HP 3 - Flammable
HP 4 - Irritant (skin irritation and eye damage)
Dispose of contents/container to an approved waste disposal plant.
Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1170	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1170	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-D See below for additional information.
IATA	UN1170	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.
This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

REACH, Annex XVII

Ethanol is subject to REACH restrictions, REACH annex XVII (entry 40).
2-methylpropan-2-ol is subject to REACH restrictions, REACH annex XVII (entry 40).

Labelling of contents according to Detergents Regulation (EC) No 648/2004

< 5%
· Anionic surfactants
· Perfumes

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Sources

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.
The Control of Major Accident Hazards Regulations (Northern Ireland) 2015.
Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.
H302, Harmful if swallowed.
H312, Harmful in contact with skin.
H315, Causes skin irritation.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H335, May cause respiratory irritation.
H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

EcoOnline

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-NIR-en